



PORTABLE & RUGGED SUBMERSIBLE ROBOTS

DTG2 STARTER



150M (500FT) DEPTH RATING
INCLUDES
50M (164FT) TETHER +
CONTROLLER +

DTG2 PRO



150M (500FT) DEPTH RATING
INCLUDES
75M (250FT) TETHER +
CARRYING CASE +
CONTROLLER

DTG2 SMART



150M (500FT) DEPTH RATING
INCLUDES
DEPTH, HEADING, TEMP SENSOR +
75M (250FT) TETHER
CARRYING CASE
CONTROLLER

DTG2 WORKER



150M (500FT) DEPTH RATING
INCLUDES
100M (330FT) TETHER +
GRABBER ARM +
DEPTH, HEADING, TEMP SENSOR
CARRYING CASE
CONTROLLER

MOST POPULAR // 4K RECORDING



150M (500FT) DEPTH RATING
INCLUDES
DTG2 SMART PACKAGE
4K CAMERA RECORDING
AUXILIARY LIGHTING

FAVORITES



AUXILIARY LIGHTS



4K CAMERA



DIGITAL VIDEO RECORDER



LASER SCALER



VIDEO GLASSES



GOPRO MOUNT



CRAWLER WHEELS



PERFORMANCE PACKAGE

3RD PARTY // ROV ADD-ONS



SONAR SYSTEMS



POSITIONING SYSTEMS



NDT TOOLS



CONTROL CONSOLE



UNDERWATER CAMERA



AUXILIARY CAMERA



SEDIMENT SAMPLER



WATER SAMPLER

DTG2 FEATURES

KEY HIGHLIGHTS



150M // 500FT



LOW-LIGHT CAMERA



UP TO 12 HOURS



UP TO 3.5 KNOTS



ONE CARRYING CASE



UNMATCHED MOBILITY



LOW MAINTENANCE

DTG2 // SPECIFICATIONS

ROV GENERAL SPECIFICATIONS:

WIDTH:	325 MM (12.8")
HEIGHT:	258 MM (10.2")
LENGTH:	279MM (11.0")
WEIGHT (IN AIR):	8.5 KG (18.7 LB)
BODY MATERIAL:	DIE CAST ALUMINUM
WINDOW MATERIAL:	ACRYLIC
DEPTH RATING:	150 M (500 FT)
OPERATING TEMP:	-5°C TO 40°C (23°F - 104°F)
SPEED:	2.5 KNOTS
WARRANTY:	1 YEAR - PARTS AND LABOUR

ROV ELECTRICAL SYSTEM:

SYSTEM VOLTAGE:	19.2 VDC
BATTERY RUN TIME:	6 - 8 HOURS
	12 HOURS (PERFORMANCE PACKAGE)
BATTERY RECHARGE:	1.5 HOURS
THRUSTER CONTROL:	INDEPENDENT
	INFINITELY VARIABLE
	100% REVERSIBLE

LIGHTS AND CAMERA:

CAMERA COLOUR:	1/3 SONY CCD	SONY ACTION CAM
	700 HD	4K VIDEO RECORDING
	0.001 LUX	
	320° RANGE OF VIEW	

FLOOD LIGHT:

	HIGH EFFICIENCY LED FLOOD
	300 LUMENS TRACKING WITH CAMERA
	1200 LUMENS WITH OPTIONAL AUXILIARY LIGHTING

ROV TETHER:

TETHER DIAMETER:	5.0 MM (0.19")
TETHER LENGTH:	50 M, 75 M, 100 M, 150 M (164 - 500 FT)
CUSTOM LENGTHS:	UP TO 400 M (1,312 FT)
TETHER WEIGHT:	NEUTRALLY BUOYANT IN WATER
TETHER CONSTRUCTION:	POLYURETHANE OUTER JACKET WITH EMBEDDED LIGHT WEIGHT SYNTHETIC FIBERS

MAXIMUM WORKING STRENGTH:	25 KG (55 LB)
MINIMUM BREAKING STRENGTH:	90 KG (200 LB)
REEL CONSTRUCTION:	HEAVY DUTY ALUMINUM ELECTRIC SLIP RING